

Rechargeable Right Angle Led #510242

Bright Star



Licht specificaties



Lumens

200



Peak beam intensity

35000cd



Runtime

4h



Beam distance

374m



Drop resistant

1M



Water resistant

1M

Afmetingen

Length: 2.5 in. (6.4 cm)

Width: 3.0 in. (7.6 cm)

Height: 7.0 in. (17.8 cm)

Kleuren

orange

Power

Lithium-Ion

Gewicht

500gr (with batteries)

Certificering

UL Protection Methods

UL 913 CSA C22.2

NFPA 70 504.2 (2008)

NFPA 1901-14.1.11.2 (2003) Certified Mounted in any Position

Intrinsically Safe

Class I, II, III DIV I, Groups C-G

Class I, II, III DIV II, Groups C-G

Operating Temp Code T3

Overige

Product Features

- Division 1 safety approved
- First RA light utilizing Lithium-Ion Technology
- Supports Alkaline or Li-Ion Battery Packs
- Impact Resistant to 1 Meter
- Ergonomically Designed Switch, for Ease of Operation
- Waterproof to 1 Meter
- 4 hour charge time
- Light weight (under 1lb)
- Battery Charge Indicator
- Low Profile Design keeps it close to your body
- Unparalleled smoke penetration.
- Emergency Light Feature:

By placing Right Angle into charging cradle with switch pressed into on position, Right Angle will automatically turn on in the absence of power.