Rechargeable Right Angle Led #510242

Bright Star





Licht specificaties

Lumens	200
Peak beam intensity	35000cd
Runtime	4h
Beam distance	374m
Drop resistant	1M
Water resistant	1M

Afmetingen

Length: 2.5 in. (6.4 cm)
Width: 3.0 in. (7.6 cm)
Height: 7.0 in. (17.8 cm)

Kleuren

orange

Power

Lithium-Ion

Gewicht

500gr (with batteries)

Certificering

UL Protection Methods
UL 913 CSA C22.2
NFPA 70 504.2 (2008)
NFPA 1901-14.1.11.2 (2003) Certified Mounted in any Position
Intrinsically Safe
Class I, II, III DIV I, Groups C-G
Class I, II, III DIV II, Groups C-G
Operating Temp Code T3

Overige

Product Features
• Division 1 safety approved
• First RA light utilizing Lithium-Ion Technology
• Supports Alkaline or Li-Ion Battery Packs
• Impact Resistant to 1 Meter
• Ergonomically Designed Switch, for Ease of Operation
• Waterproof to 1 Meter
• 4 hour charge time
• Light weight (under 1lb)
• Battery Charge Indicator
• Low Profile Design keeps it close to your body
• Unparalleled smoke penetration.
• Emergency Light Feature:
By placing Right Angle into charging cradle with switch pressed into on position, Right Angle will automatically turn on in the absence of power.